

## 60 cm Ku-Band receive-only antenna system



- DS-4060 - Universal feed support
- DS-4061 - D-tube feed support
- DS-4062 - RCA style feed support

Winegard Company has been designing and manufacturing television reception products for over 46 years. Satellite television reception products have been a major part of our business for over 20 of those years.

We currently manufacture digital satellite antennas for direct-to-home installations in 46, 60, 76 cm, and 1 and 1.9 meter sizes.

Winegard reflectors are designed using the CAD-CAM process. Galvanized steel, used in manufacture, is carbon sheet steel with a zinc-iron alloy coating. Corrosion resistant, these alloys react to scratches and other damage through galvanic action between steel and zinc — the zinc protects breaks in the coating and prevents further damage after installation. Reflectors are checked repeatedly during manufacturing with a computer numerical control coordinate measuring machine. The CNC CMM is one of the best methods of quality control, from design to fabrication. Antennas are checked at 49 points during fabrication processes to maintain quality and precision.

The combination of powder coat finish, E-Coat and JS-600 finished hardware gives our reflectors and mounts a proven, superior weatherproof finish.

In addition to the manual for each product, technical support is available by phone or telefax. Winegard DTH products, made in the U.S.A., are backed by a limited five year warranty.

### Mechanical

Optics .....	Offset
Effective aperture .....	60 cm (23.7 in.)
Antenna height .....	70 cm (27.4 in.)
Antenna width .....	64 cm (25.3 in.)
Galvanized steel .....	20 ga.
Weight, antenna only .....	2.25 Kg. (5 lbs.)
F/D .....	.59
Offset angle .....	24°
Focal distance .....	35.2 cm (13.87 in.)
Surface accuracy .....	.014 - .018 in. average
Elevation range .....	10° to 90°
Mounting options .....	Universal

### Electrical

Frequency range .....	10.95-12.75 GHz		
Gain at mid-band			
	11.2	12.1	12.6
	35.55 dBi	36.22 dBi	36.57 dBi
Aperture efficiency .....	73%		
Cross polarization (on axis) .....	-21 dB		
Beamwidth at -3 dB .....	2.8°*		
Beamwidth at -10 dB .....	4.8°*		

### Environmental

Wind loading	
Operational .....	80.5 Km/hr. (50 mph.)
Survival .....	161 Km/hr. (100 mph.)
Atmosphere .....	10 yrs.

### Feed support options

Rectangular type	Universal
D-tube	

\* Gain, efficiency and pattern measured/calculated with Winegard proprietary circularly polarized feed horn at 12.45 GHz.  
All data obtained from independent certified test facilities. Detailed patterns available on request.



# WINEGARD®

## 60 cm

Winegard's 60 cm — designed for easy installation, it has 360° azimuth and 10° to 90° elevation adjustments. Feed support systems are available for all popular brands of LNBFs.

The reflector is manufactured from 20 gauge galvanized steel, finished with a seven step, textured thermoset powder coat. A hydrophobic additive in the finish increases water and snow repellent action. The mount, manufactured from galvanized steel, is E-Coated for maximum protection. All hardware has the highly corrosive resistant JS-600™ finish. The combination of these processes gives Winegard DTH systems the best finish available!

The antenna, mount and hardware have had extensive atmospheric testing, and will withstand 700 hours of salt spray. This system is designed to operate in winds up to 50 mph and survive winds of 100 mph.

The system includes a comprehensive manual, plus a technical support telephone number. It has Winegard's five-year limited warranty, and is UPS shippable.



### **Universal Mount**

**Precision-stamped** for consistent quality

**Easy to install.** All hardware same size, only one wrench needed.

**Galvanized steel** antenna and galvanized steel mount with a combination of powder coat, E-coat and JS-600 finishes for outstanding environmental durability

**Design** meets 100 mph wind loading requirements

**Responsive customer service** support

**60 cm Ku-Band  
receive-only antenna system**